

12#9's, epoxy coated, spaced as shown, top and bottom placed parallel to deck overhang steel. Hook one end.

Provide slip hole or drill and tap box for 1/4" ϕ conduit.

ϕ 4" ϕ conduit, full length of bridge.

#5 \hook top and bottom epoxy coated.

ϕ Parapet control joint.

5-#5 \hook Ties

Spacing to match that of deck overhang steel (Varies 5" to 7"). Bars to be placed between deck overhang steel.

8-#5 \hook Ties, epoxy coated, @ 8" c/c See Sheet 2 of 2.

Parapet

ϕ Parapet control joint.

ϕ Bracket

See "Note A"

1'-10"

A/2

A (Minimum 6'-5") See Note B

PLAN

Scale: 1/2"=1'-0"

Note B:

Station for light post support bracket shown on Plans is only approximate. ϕ Bracket to be located midway between parapet control joints. A= Normal parapet control joint spacing (Adjust as necessary to meet minimum limitations). If a light post is placed at ϕ of pier, eliminate the control joint at the ϕ of pier. The first control joint beyond, on one side only shall be changed to a paraffin joint.

Note:

Deck overhang reinforcing steel not shown.

Note A:

Contractor is to contact the District Engineer in writing prior to placing sleeves for anchor bolts, to ascertain the bolt circle dimension and size of anchor bolts that will be used on this project. All light poles to be set plumb using leveling nuts on anchor bolts. Max. height of pole for this detail is 40'.

1/2" ϕ Drain at low point of junction box.

6" x 6" x 8" galvanized cast iron, galvanized steel or fiberglass U.L. listed junction box with cover. Provide holes in box for 4" ϕ conduit.

ϕ 4" ϕ conduit

#5 \hook Ties

#5 \hook Ties. See Sheet 2 of 2.

Sleeves for anchor bolts. See "Note A."

Bottom to match underside of fascia, parallel to grade.

SECTION A-A

Scale: 1/2"=1'-0"

For Section "B-B" see Sheet 2 of 2.

42" DIAMOND BACK

APPROVAL	
<i>E. S. Friedman</i>	DIRECTOR
	OFFICE OF BRIDGE DEVEL.
DATE: 6/1/05	
REVISIONS	
SHA	FHWA
11-26-07	
1-9-08	
FHWA APPROVAL	
DATE:	

STATE OF MARYLAND
DEPARTMENT OF TRANSPORTATION
STATE HIGHWAY ADMINISTRATION
OFFICE OF BRIDGE DEVELOPMENT

SUPPORT BRACKET FOR BRIDGE MOUNTED LIGHT POST WITH SINGLE CONDUIT AND 42" F-SHAPE PARAPET WITH DIAMOND BACK



STANDARD NO. BR-SS(6.28)-05-167B(L)

SHEET 1 OF 2

SUPER-CONCRETE WORK